RAMMER 4099E

EXCELLENCE LINE



FACTORY INSTALLED RD3 FOR MYFLEET


- RAMVALVE
- RAMLUBE II (OPT.)
- MEMBRANE TYPE ACCUMULATOR
- DOUBLE TOOL RETAINING PIN STRUCTURE
- FBE (FIXED BLOW ENERGY)
- UPGRADED GREASING FOR TOOL BUSHINGS
- VIDAT TIE RODS
- EASY IBP ADJUSTMENT
- HARD WEAR PLATES
- SIMPLE LOWER TOOL BUSHING ROTATING OR REPLACEMENT
- ACCUMULATOR FILLING POINT ON SIDE
- STROKE SELECTOR


EXCELLENCE LINE HITS SMARTER

The Rammer Excellence Line is a set of state-of-the-art hydraulic hammers for all your rock breaking needs. All Excellence Line hammers now have integrated smart technology for easier fleet management and more efficient processes.

Read more about the product from www.rammer.com/excellence

Rammer®





SPECIFICATIONS

Minimum working weight, kg (lb)	3380-3540 (7450-7800)
Impact rate, Long Stroke, bpm	400-560
Impact rate, Short Stroke, bpm	520-700
Operating pressure	150-160 (2175 - 2320)
Pressure relief, min bar (psi)	210 (3045)
Pressure relief, max bar (psi)	230 (3335)
Oil flow range, l/min (gal/min)	250-350 (66.0-92.5)
Back pressure, max bar (psi)	12 (175)
Input power, kW (hp)	93 (125)
Tool diameter, mm (in)	166 (6.54)
Carrier weight, allowed range, t (lb)	36-55 (75000-121300)
Noise level, measured sound power level, LWA, dB	126
Noise level, guaranteed sound power level, LWA, dB	130

TOOLS

Chisel
Hard rock chisel
Limestone chisel
Moil point
Pyramid
Blunt
Super blunt

PARTS

Service kit 1
Service kit 2
Special tool grease
Meissel paste

Specifications are subject to change without notice

Walkers Hammers
Hydraulic Attachment Specialist
03 9315 3788
sales@walkershammers.com.au
3, 4-6 Somerleigh Rd
Laverton North VIC 3026
walkershammers.com.au

Rammer®